

The Valspar Corporation

Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Material Identification

Product ID: DR03
Product Name: GOLD SPARKLE DR-3
Product Use: Chemical intermediate.
Date Published: 2004/10/09
Revision Date: 2000/11/01

Company Identification

The Valspar Corporation
1101 Third Street South
Minneapolis, MN 55415
Manufacturer's Phone: 1-612-332-7371

**24-Hour Medical Emergency
Phone:** 1-888-345-5732

2. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

| Common Name CAS # | Approx Wt% | Chemical name |
|---------------------------------------|---------------|----------------------------|
| Trade Secret : PROPRIETARY INERT | 60 - 65 | PROPRIETARY INERT |
| Trade Secret : PROPRIETARY PIGMENT | 20 - 25 | PROPRIETARY PIGMENT |
| CRYSTALLINE SILICA 14808-60-7 | 5 - 10 | QUARTZ (SiO ₂) |
| Trade Secret : PROPRIETARY PIGMENT | 1 - 5 | PROPRIETARY PIGMENT |

If this section is blank there are no hazardous components per OSHA guidelines.

3. HAZARDS IDENTIFICATION

Primary Routes of Exposure:

Inhalation
Ingestion
Skin absorption

Emergency Overview:

This section not in use.

This product contains ingredients that may contribute to the following potential acute health effects:

Inhalation Effects:

None known.

Eye Contact:

None known.

Skin Contact:

None known.

Acute Ingestion:

None known

Other Effects:

None known

This product contains ingredients that may contribute to the following potential chronic health effects:

See Section 11 for toxicological information about Mutagens, Teratogens and Carcinogens.

If this section is blank, no information is available.

4. FIRST AID MEASURES

Inhalation:

If affected by inhalation, move victim to fresh air. If symptoms persist, seek medical attention.

Eye Contact:

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

Skin Contact:

In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. If irritation persists get medical attention.

Ingestion:

If swallowed, contact medical personnel immediately to determine best course of action.

Medical conditions aggravated by exposure: Any respiratory or skin condition.

5. FIRE FIGHTING MEASURES

| | |
|----------------------------------|--|
| Flash point (Fahrenheit): | 201° F (94° C) TCC/PM |
| Lower explosive limit: | Not available. % |
| Upper explosive limit: | Not available. % |
| Autoignition temperature: | Not available.° F (° C) |
| Sensitivity to impact: | No. |
| Sensitivity to static discharge: | Sensitivity to static discharge is not expected. |
| Hazardous combustion products: | See Section 10. |

Unusual fire and explosion hazards:

None known.

Extinguishing media:

Carbon dioxide, dry chemical, foam and/or water fog.

Fire fighting procedures:

Use water spray to cool nearby containers and structures exposed to fire.

6. ACCIDENTAL RELEASE MEASURES**Action to be taken if material is released or spilled:**

Avoid contact with eyes.

7. HANDLING AND STORAGE**Precautions to be taken in handling and storage:**

Keep container closed when not in use.

8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS**Personal Protective Equipment****Eye and face protection:**

Avoid contact with eyes. Wear chemical goggles if there is the possibility of contact or splashing in the eye.

Skin protection:

Appropriate chemical resistant gloves should be worn. To prevent skin contact wear protective clothing covering all exposed areas.

Respiratory protection:

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

Ventilation

Required when spraying or applying in confined area.

Exposure Guidelines**OSHA Permissible Exposure Limits (PEL's)**

| Common Name CAS # | Approx Wt% | TWA (final) | Ceilings limits (final) | Skin designations |
|---------------------------------------|---------------|---------------------------------------|-------------------------|-------------------|
| Trade Secret : PROPRIETARY INERT | 60 - 65 | see Table Z-3 | | |
| Trade Secret : PROPRIETARY PIGMENT | 20 - 25 | 15 mg/m ³ TWA (total dust) | | |
| CRYSTALLINE SILICA 14808-60-7 | 5 - 10 | see Table Z-3 | | |
| Trade Secret : PROPRIETARY PIGMENT | 1 - 5 | 10 mg/m ³ TWA | | |

ACGIH Threshold Limit Value (TLV's)

| Common Name CAS # | Approx Wt% | TWA | STEL | Ceiling limits | Skin designations |
|----------------------|---------------|-----|------|----------------|-------------------|
|----------------------|---------------|-----|------|----------------|-------------------|

| | | | | | |
|---------------------------------------|---------|--|--|--|--|
| Trade Secret : PROPRIETARY INERT | 60 - 65 | 3 mg/m3 TWA (this TLV is for the respirable fraction of dust for Mica)' for particulate matter containing no asbestos and <1% crystalline silica | | | |
| Trade Secret : PROPRIETARY PIGMENT | 20 - 25 | 10 mg/m3 TWA | | | |
| CRYSTALLINE SILICA 14808-60-7 | 5 - 10 | 0.05 mg/m3 TWA (this TLV is for the respirable fraction of dust) | | | |
| Trade Secret : PROPRIETARY PIGMENT | 1 - 5 | 5 mg/m3 TWA (welding fumes, dust, total particulate as Fe) | | | |

If this section is blank, no information is available.

9. PHYSICAL PROPERTIES

Odor: Normal for this product type.
Physical State: Liquid
pH: Not determined.
Vapor pressure: Not determined. mmHG @ 68° F (20° C)
Vapor density (air = 1.0): Not determined.
Boiling point: Not available.° F (Not Available.° C)
Solubility in water: Insoluble.
Coefficient of water/oil distribution: Not determined.
Density (weight per gallon): 24.7
Specific gravity (water = 1): 2.96
Evaporation rate (butyl acetate = 1.0): Not determined.

10. STABILITY AND REACTIVITY

Stability: This product is stable.
Conditions to Avoid: None known.
Incompatibility: None known.
Hazardous Polymerization: None anticipated.
Hazardous Decomposition Products: Silicon dioxide. Metal oxide fumes.

Sensitivity to static discharge: Sensitivity to static discharge is not expected.

11. TOXICOLOGICAL INFORMATION

| Common Name CAS # | Approx Wt% | IARC Group 1 - Human Evidence | IARC Group 2A - limited human data | IARC Group 2b - sufficient animal data |
|----------------------|---------------|----------------------------------|---------------------------------------|---|
|----------------------|---------------|----------------------------------|---------------------------------------|---|

| | | | | |
|----------------------------------|--------|---|--|--|
| CRYSTALLINE SILICA 14808-60-7 | 5 - 10 | Monograph 68, 1997; (inhaled in the form of quartz or cristobalite from occupational sources) | | |
|----------------------------------|--------|---|--|--|

| Common Name CAS # | Approx Wt% | NTP Known carcinogens | NTP Suspect carcinogens | NTP Evidence of carcinogenicity |
|----------------------------------|---------------|--------------------------|----------------------------|------------------------------------|
| CRYSTALLINE SILICA 14808-60-7 | 5 - 10 | Known Carcinogen | | |

| Common Name CAS # | Approx Wt% | OSHA Select carcinogens | OSHA Possible select carcinogens | ACGIH Carcinogens |
|----------------------------------|---------------|----------------------------|-------------------------------------|------------------------------------|
| CRYSTALLINE SILICA 14808-60-7 | 5 - 10 | | | A2 - Suspected Human Carcinogen |

If this section is blank, no information is available.

12. ECOLOGICAL DATA

Not available at this time.

13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORTATION INFORMATION

U.S. Department of Transportation

Proper Shipping Name: PIGMENT

49 CFR Hazardous Material Regulations Parts 100-180

The supplier will apply the combustible liquid exception in 49 CFR 173.150(f), limited quantity or "does not sustain combustion" exceptions and consumer commodity rules, when authorized. Please check 49 CFR Parts 100-180 to determine if the use of these exceptions applies to your shipments when re-shipping our products.

International Air Transport Association:

Proper Shipping Name: PIGMENT

International Maritime Organization:

Proper Shipping Name: PIGMENT

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

SARA 311/312 Hazard Class:

Acute: Yes
Chronic: Yes
Flammability: No
Reactivity: No
Sudden Pressure: No

Product ID: DR03

U.S. STATE REGULATIONS:

Pennsylvania Right To Know:

| | |
|---------------------|--------------|
| CRYSTALLINE SILICA | 14808-60-7 |
| PROPRIETARY PIGMENT | Trade Secret |
| PROPRIETARY PIGMENT | Trade Secret |
| PROPRIETARY INERT | Trade Secret |

California Proposition 65:

WARNING: This product contains a chemical known to the State of California to cause cancer.

Rule 66 status of product Not photochemically reactive.

INTERNATIONAL REGULATIONS - Chemical Inventories

TSCA Inventory: All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

Canada Domestic Substances List: All components of this product are listed on the Domestic Substances List.

16. OTHER INFORMATION

HMIS Codes

| | |
|----------------------|--|
| Health: | 2 |
| Flammability: | 1 |
| Reactivity: | 0 |
| PPE: | X - See Section 8 for Personal Protective Equipment (PPE). |

Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

Disclaimer:

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this

product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.