

UC25 KOSMIC KANDY KARRIER

(APPENDIX "A")

Rule 1151 & Rules 4602 & 4612 Phase II

GENERAL INFORMATION

Kosmic Kandy Karrier UC25 is a 2.1 VOC product that meets the VOC's for SCAQMD Rule 1151 and SJVAQMD Rule 4602 & 4612 Phase II compliancy. UC25 is designed to be used as a carrier for our KK Koncentrates to duplicate our UK Kandy Kolors over our Shimrin® Base Coats. UC25 is medium solids, 30% solids as applied, and has the same application properties as our conventional UK Kandy's. UC25 features excellent clarity. It has excellent weathering and ultraviolet resistance.



• REFER TO OUR TECH SHEET ON UC25 / KK URETHANE KANDY MIX RATIOS & APPLICATION

TECHNICAL DATA (See Low VOC Data Sheet For Specific Values For Each Product)



- Coatings Category: Color Coating
- Actual VOC RTS less exempt solvents: 0.60 lbs./gal. (72.4 g/L) max.
- Regulatory VOC RTS less exempt compounds: 1.59 lbs./gal. (191 g/L) max.
- Density: 10.23 lbs./gal. (1228.0 g/L) (Max. VOC Color)
- Weight % Volatiles: 71.8%
- Weight % exempt compounds: 65.9%
- Weight % water: 0%

HEATH AND SAFETY

IMPORTANT The contents of this package have to be blended with other components before the product can be used. Before opening the packages, be sure you understand the warning messages on the labels of all components, since the mixture will have the hazards of all its parts. Improper spray technique may result in a hazardous condition. Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

See Material Safety Data Sheet and Labels for additional safety information and handling instructions.